

College of Tropical Agriculture and Human Resources University of Hawai'i at Mānoa

# Sprayer Calibration Using the 1/128th Method for Boom Spray Systems

Jensen Uyeda,<sup>1</sup> Jari Sugano,<sup>2</sup> Steve Fukuda,<sup>3</sup> Mike Kawate,<sup>2</sup> Robin Shimabuku,<sup>2</sup> and Koon-Hui Wang<sup>2</sup> <sup>1</sup>Tropical Plant and Soil Sciences, <sup>2</sup>Plant and Environmental Protection Sciences, <sup>3</sup>O'ahu County Extension

alibrating spray equipment is an important step in applying crop-protection chemicals to a targeted area. Proper calibration will help ensure accurate spray coverage (usually measured in gallons per acre, or GPA). The 1/128th method of sprayer calibration is a simplified way to calibrate most boom spray systems. It is based on the ratio of 1 gallon, or 128 fluid ounces, to 1/128th of an acre, or 340 square feet (sq ft). The 1/128th calibration method is a fast and easy way to compute the gallon-per-acre rate (GPA). Under-application of crop-protection chemicals can result in pest-control and pest-resistance issues. And over-application of crop-protection chemicals can lead to human, legal, and environmental issues and crop injury, i.e., phytotoxicity. It is important to know the calibrated spray volume (GPA) and the amount of pesticide to be mixed with that calibrated spray volume to accurately apply crop-protection chemicals. Always read the pesticide label and follow its instructions.

# Simplified 1/128th Calibration Conversions

#### 128 fluid ounces = 1 gallon

1 fluid ounce = 1/128th of a gallon

# 340 sq ft = 1/128th of an acre

Based on the 1/128th calibration method, each ounce of water collected during calibration corresponds to 1 gallon of spray mix per acre.

# 1 fluid ounce collected $\rightarrow$ 1 gallon per acre (GPA)



This 1/128th calibration method requires almost no calculations. The number of fluid ounces of spray mix you apply to a 340 sq ft area corresponds to the estimated number of gallons of spray mix per acre.

# Key Spray Variables to Consider for Boom Sprayer Application

- Properly maintained spray equipment
- Spray pump pressure
- Spray nozzle pressure; e.g., length and size of hose
- Spray aperture setting
- Spray nozzle orifice size
- Target pest
- Pest incidence
- Crop height
- Crop density
- Wind speed, direction
- Field terrain; e.g., slope, weeds, etc.
- Tractor speed

Published by the College of Tropical Agriculture and Human Resources (CTAHR) and issued in furtherance of Cooperative Extension work, Acts of May 8 and June 30, 1914, in cooperation with the U.S. Department of Agriculture, under the Director/Dean, Cooperative Extension Service/CTAHR, University of Hawai'i at Mānoa, Honolulu, Hawai'i 96822. Copyright 2011, University of Hawai'i. For reproduction and use permission, contact the CTAHR Office of Communication Services, cos@ctahr.hawaii.edu, 808-956-7036. The university is an equal opportunity/affirmative action institution providing programs and services to the people of Hawai'i without regard to race, sex, gender identity and expression, age, religion, color, national origin, ancestry, disability, marital status, arrest and court record, sexual orientation, or status as a covered veteran. Find CTAHR publications at www.ctahr.hawaii.edu/freepubs.

# Calibrating Your Boom Sprayer Using the 1/128th Calibration Method

# Step 1

Measure a test area equal to 1/128th of an acre (340 sq ft) (Fig. 1a, b), taking the length of your boom system into account.

The boom may be 10 ft by 34 ft or 20 ft by 17 ft (Fig. 1c). Note that you do not need to use the exact dimensions provided in the example below. What is important is to establish a 340 sq ft area, or 1/128th of an acre.

<u>For best results</u>, measuring the area in the field to be sprayed is ideal, as crops vary in height and density. Selecting a good representative crop area for calibration purposes will help ensure that the correct amount of cropprotection chemical is applied to the actual target area.

#### Step 2

Spray water on the plants at a consistent speed to get the best spray coverage of the targeted 340 sq ft area (Fig. 2a, b).

Take into account the height and foliage density of the developing crop during calibration (Fig. 2c, d). As plant density increases, it may take more spray volume, a longer time, or both to spray a given area.













ADJUSTING FOR CROP TYPE



# Step 3

Measure the time it takes you to spray the targeted area (Fig. 3).

# Step 4

Repeat Step 3 several times and average the times (Fig. 4). Example: It took an average of 50 seconds to spray the targeted area.

# Step 5

Spray water from each nozzle into its own container for the average time it took you to spray the targeted area (Fig. 5a, b). Example: Spray water into containers for 50 seconds, leaving all other spray variables (e.g., spray pressure) unchanged.

This process also allows you to determine whether all nozzles are emitting the proper amount of cropprotection chemicals. If the output is more than 10% different from the average of all nozzles, clean or replace nozzles that are clogged, worn, or damaged (Fig. 5c).





#### Step 6

Combine all collected liquid into one measuring container and measure the amount of water collected in fluid ounces (Fig. 6).

# Step 7

The amount of water collected in fluid ounces corresponds to your calibrated spray volume in gallons of spray mix per acre. Example: You calculated 64 fluid ounces in the time it took to spray the targeted area (340 sq ft). Therefore, based on your calibration, the sprayer output is 64 gallons per acre, or 64 GPA (Fig. 7).

# Summary

Proper sprayer calibration is an important step in overall pest and disease management. A change in one aspect of pesticide application (e.g., spray pressure, nozzle type, speed, etc.) can drastically influence the results. Spray equipment should be recalibrated at the beginning of each application, as conditions often change. A change in the person spraying, for example, can also affect calibration.

Knowing how much product is applied to your crop is essential. Under-applying chemical products can result in poor pest control and increased pest resistance, as well as increased production costs and financial losses; overapplication of chemical products can lead to problems with human health, legal issues, or environmental and crop injury concerns such as phytotoxicity. Remember, always read and follow the label of the pesticide you are applying. For more information, contact the Hawai'i Department of Agriculture Pesticide Branch or the UH CTAHR Extension Service.

# References

- Cromwell, R. 2002. 1/128 of an Acre Method of Sprayer Calibration. University of Florida. AE-5. http://edis. ifas.ufl.edu/AE012
- Ferrell, M.A. 1998. 1/128 Method of Calibration Calibrating Hand Sprayers and High Pressure Hand Guns. College of Agriculture, University of Wyoming fact sheet. MP-93.3. http://www.wyomingextension. org/agpubs/pubs/MP93\_Series/mp93-3.pdf
- Privette, C.V., and R.G. Bellinger. 2002. Calibration of Pesticide Application Equipment Using the 1/128<sup>th</sup> Method. Clemson University Pesticide Information Program information sheet. PIP-38. http://www. clemson.edu/extension/pest\_ed/pdfs/pipsheets/ pip38128.pdf

# Disclaimer

Mention of a trademark or proprietary name does not constitute an endorsement, guarantee, or warranty by the University of Hawai'i Cooperative Extension Service or its employees and does not imply a recommendation to the exclusion of other suitable products. Pesticide use is governed by state and federal regulations. Read the pesticide label to be sure that the intended crop site is included on it, and follow all label directions.

# Note on Measurements

We use fluid ounces, gallons, ounces, pounds, etc. to correspond with pesticide labels.

# Acknowledgements

The authors thank Fred Brooks and Charles Nagamine of Plant and Environmental Protection Sciences for their substantial contributions to this publication.



